

# PRODUCT DATA SHEET #702 TPO Primer

# **USES**

AIM #702 TPO Primer is an adhesion promoter intended to aid adhesion of 100% silicone and silane-terminated polyurethane coatings and sealants to new and aged TPO roofing membranes.

#### **DESCRIPTION**

AIM #702 is manufactured from a fast evaporating solvent carrier and adhesive resins. A blue pigment is added to the standard product so that the applicator can better gauge application rates.

#### **APPLICATION**

All surfaces must be clean and completely dry. Apply AIM #702 with a short nap roller or brush at the rate of one gallon per 800-1000 sq. ft. Applications should be as thin as possible. Allow one to two hours before applying coatings or sealants.

The above application information\on is a summary for reference only. Please contact AIM Technical Service for more information related to the application of this product before quoting or starting any project.

Clean up: Wet material can be cleaned with soap and water. Dried material can be cleaned with mineral spirits. Use care when handling solvents.

Shelf Life: Two years from the date of manufacture.

### **CAUTION**

## **COMBUSTIBLE LIQUID AND VAPOR**

Contains petroleum distillate. Harmful or fatal if swallowed.

Vapor harmful. May affect the brain or central nervous system causing dizziness, headache, or nausea. Causes nose and throat irritation. Causes eye irritation. Causes skin irritation. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

Keep away from heat and open flame. Use only with adequate ventilation. Do not breathe vapors. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling

#### KEEP OUT OF REACH OF CHILDREN

**First Aid:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

Warning: This product contains a chemical known to the State of California to cause cancer.

## **SPECIFICATIONS**

Viscosity	ASTM D 1296	50 cps
Solids by Weight	ASTM D 1644	2%
Solids by Volume	ASTM D 2697	2%
Weight Per Gallon	ASTM D 1147	10 lbs.
Flash Point	ASTM D 56	105°F / 41°C
VOC	EPA 24	< 100 g/l

Container Sizes: Quart, 1, 5, 55 gallon

Colors: Blue and Clear



# **LIMITED WARRANTY**

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of 12 months from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application.

LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.



6505 West Park Boulevard • Suite 306-366 • Plano, TX 75093 • (214) 254-4720