



# PRODUCT DATA SHEET

## #200 Non-Fibrated Roof Coating

### USES

AIM #200 Non-Fibrated Roof Coating provides an economical means of recoating and preserving smooth-surface asphalt roofs. Periodic recoating of otherwise sound built-up roofing felts can prolong service life many years. Deteriorated roofs can often be restored with the use of polyester fabric and select asphalt coatings. This product is not intended for use over tar or asphalt and gravel roofs. AIM 200 Non-Fibrated Roof Coating also provides an economical means for damp proofing concrete foundation walls.

### DESCRIPTION

AIM 200 Non-Fibrated Roof Coating is formulated from refined, low softening point asphalt and petroleum solvents. Consistency is maintained to provide easy brushing qualities. This product is ready to use and does not require special preparation before use.

### APPLICATION

Surface to be coated must be clean and dry. Weak, broken, cracked or blistered areas of the roof and flashings must be repaired prior to coating with AIM 200 Non-Fibrated Roof Coating. Blisters, which are caused by trapped moisture, must be opened and dried, then resealed using glass membrane and Plastic Roof Cement. Moisture trapped between plies of a roof will eventually reappear as a blister or a leak. Apply AIM 200 Non-Fibrated Roof Coating evenly, as it comes from the container with any appropriate tool, preferably, a four knot roofing brush, at the rate of approximately one to two gallons per 100 square feet. Do not allow foot traffic until the coating is fully cured. Clean up with mineral spirits or waterless hand cleaner. Use care in handling solvents.

### CAUTION

#### COMBUSTIBLE LIQUID AND VAPOR

Contains petroleum distillate. Harmful or fatal if swallowed.

Vapor harmful. May affect the brain or central nervous system causing dizziness, headache, or nausea. Causes nose and throat irritation. Causes eye irritation. Causes skin irritation. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

Keep away from heat and open flame. Use only with adequate ventilation. Do not breathe vapors. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

### KEEP OUT OF REACH OF CHILDREN.

**First Aid:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

**Warning:** This product contains a chemical known to the State of California to cause cancer.

### SPECIFICATIONS

Applicable Specification	None	% Asphalt	70 min.
Viscosity	ASTM D-562	% Solids	65 min.
	450 g @ 77°F (25°C) 2200 cps	% Non-volatile	80 max.
Recommended rate of application	1 to 2 gal. Per 100 sq. ft.	Weight per gallon	7.9 lbs. (+/- 0.4 lb)
		Flash Point (TCC)	100°F + (38.7°C)
Container Sizes	5 Gallon		



#### **LIMITED WARRANTY**

**TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.**

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of 12 months from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application.

**LIMITATION OF LIABILITY:** In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

