



PRODUCT DATA SHEET

#300 Plastic Roof Cement

USES

AIM #300 Plastic Roof Cement is a trowel-applied Plastic Cement used to install, repair or rebuild roof flashings at parapet walls, gravel stops, stacks, vents, monitors and similar applications. AIM #300 Plastic Roof Cement may be used with fiberglass, polyester fabrics or roll roofing for permanent repairs.

DESCRIPTION

AIM #300 Plastic Roof Cement is manufactured from Type I Roofing Asphalt, petroleum solvents and non-asbestos reinforcing fibers. It applies fast and smooth and breaks cleanly off the trowel without stringing.

APPLICATION

The surface to be repaired must be clean, dry and free of debris. Apply AIM #300 Plastic Roof Cement evenly with a pointed roofer's trowel or gloved hand. AIM #300 Plastic Roof Cement should be applied 1/8 to 1/4 of an inch thick and may be reinforced with glass membrane or polyester fabric to strengthen the repair. When making a permanent repair to a blister, open up the area and allow it to dry thoroughly. Clean up with mineral spirits or waterless hand cleaner. Use care when handling solvents.

CAUTION

COMBUSTIBLE LIQUID AND VAPOR

Contains petroleum distillate. Harmful or fatal if swallowed.

Vapor harmful. May affect the brain or central nervous system causing dizziness, headache, or nausea. Causes nose and throat irritation. Causes eye irritation. Causes skin irritation. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

Keep away from heat and open flame. Use only with adequate ventilation. Do not breathe vapors. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.

First Aid: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

Warning: This product contains a chemical known to the State of California to cause cancer.

SPECIFICATIONS

Applicable Specification	D-4586	% Asphalt	48 min.
Recommended rate of application	1/8 to 1/4 inch thick	% Solids	71 min.
Container Sizes	3, 5 Gallon	% Non-volatile	84 max.
		% Mineral Filler Content	14 min.
		VOC	<250 g/l max.
		Weight per gallon	9.4 lbs. (+/- 0.4 lb/gal)
		FlashPoint(TCC)	+100°F (38.7°C)



LIMITED WARRANTY

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of 12 months from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application.

LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.



6505 West Park Boulevard • Suite 306-366 • Plano, TX 75093 • (214) 254-4720