



PRODUCT DATA SHEET

#350 Premium Modified Flashing Cement

USES

AIM #350 Premium Modified Flashing Cement is a premium grade trowel-applied Flashing Cement used to install, repair or rebuild roof flashings at parapet walls, gravel stops, stacks, vents, monitors and similar applications. AIM #350 may be used with fiberglass, polyester fabrics or roll roofing for permanent repairs. This product is may be applied to wet and underwater surfaces.

DESCRIPTION

AIM #350 is manufactured from higher softening point asphalt, petroleum solvents, reinforcing fibers and a special water displacing additive. It applies fast and smooth and breaks cleanly off the trowel without stringing. AIM 350 is designed for adhering SBS modified bitumen membranes to flashings and other vertical surfaces. AIM 350 can be used for flashing around vents, pipes, skylights and other roof penetrations as well as for patching high movement areas on SBS and asphalt built-up roofs.

APPLICATION

The surface to be repaired must be clean, dry and free of debris. Apply AIM #350 evenly with a pointed roofer's trowel or gloved hand. AIM #350 should be applied 1/8 to 1/4 of an inch thick and may be reinforced with polyester fabric to strengthen the repair. When making a permanent repair to a blister, open up the area and allow it to dry thoroughly. In order to adhere to wet surfaces, apply the product in one direction with sufficient force to displace the water from underneath it.

Clean up with mineral spirits or waterless hand cleaner. Use care when handling solvents.

CAUTION

COMBUSTIBLE LIQUID AND VAPOR

Contains petroleum distillate. Harmful or fatal if swallowed.

Vapor harmful. May affect the brain or central nervous system causing dizziness, headache, or nausea. Causes nose and throat irritation. Causes eye irritation. Causes skin irritation. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

Keep away from heat and open flame. Use only with adequate ventilation. Do not breathe vapors. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.

First Aid: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

Warning: This product contains a chemical known to the State of California to cause cancer.



6505 West Park Boulevard • Suite 306-366 • Plano, TX 75093 • (214) 254-4720

SPECIFICATIONS

Applicable Specification	ASTM D 4586 Type I, Class II ASTM D 3019 Trowel	% Solids % Non-volatile ASTM D-6511 Weight per gallon Elongation ASTMD-412 Recovery (nominal) Flash Point	70 min. 80 max. 8.5 lbs. 200%* 95% min. +100°F (38.7 °C)
Viscosity			
Recommended rate of application	1/8 to 1/4 inch thick		
Container Sizes	3, 5 Gallon		



LIMITED WARRANTY

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of 12 months from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application.

LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.



6505 West Park Boulevard • Suite 306-366 • Plano, TX 75093 • (214) 254-4720