



PRODUCT DATA SHEET

#360 Premium Modified Wet/Dry Elastomeric Flashing Cement

USES

AIM #360 Premium Wet/Dry Elastomeric Flashing Cement is an asphalt based roof cement designed for repairing roofs and roof flashings that are wet or under water. This permits repairs immediately and can prevent more extensive water damage.

DESCRIPTION

AIM 360 Premium Wet/Dry Elastomeric Flashing Cement is manufactured from Type I Roofing Asphalt, polymer modifiers, reinforcing fibers, petroleum solvents and a special additive which displaces moisture and allows application to wet surfaces.

APPLICATION

The surface to be repaired must be clean and free of debris. Apply AIM 360 Premium Wet/Dry Elastomeric Flashing Cement evenly with a pointed roofer's trowel or gloved hand. Use sufficient pressure to force water out from underneath the mastic as it is applied. AIM 360 Premium Wet/Dry Elastomeric Flashing Cement should be applied 1/8 to 1/4 of an inch thick and may be reinforced with glass membrane or polyester fabric to strengthen the repair. Repairs made to wet surfaces should be considered temporary as trapped moisture will expand when heated by the sun causing blisters and potentially new leaks. When making a permanent repair, open up the area and allow it to dry thoroughly. Clean up with mineral spirits or waterless hand cleaner. Use care when handling solvents.

CAUTION

COMBUSTIBLE LIQUID AND VAPOR

Contains petroleum distillate. Harmful or fatal if swallowed.

Vapor harmful. May affect the brain or central nervous system causing dizziness, headache, or nausea. Causes nose and throat irritation. Causes eye irritation. Causes skin irritation. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

Keep away from heat and open flame. Use only with adequate ventilation. Do not breathe vapors. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.

First Aid: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

Warning: This product contains a chemical known to the State of California to cause cancer.

SPECIFICATIONS

Applicable Specification	ASTM D 4586 Type I, Asbestos Free	Wet Adhesion ASTM D-3409	100%
Viscosity	Trowel	% Asphalt ASTM D-6511	45 min.
Recommended rate of application	1/8 to 1/4 inch thick	% Solids ASTM D-6511	70 min.
Container Sizes	3, 5 Gallon 10.1 oz. tubes	% Non-volatile ASTM D-6511	86 max.
		Weight per gallon	8.5 lbs.
		Flash Point (TCC)	+100°F (38.7°C)
		VOC	Less than 250 g/l





LIMITED WARRANTY

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of 12 months from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application.

LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.



6505 West Park Boulevard • Suite 306-366 • Plano, TX 75093 • (214) 254-4720