



PRODUCT DATA SHEET

#410 Non-Fibrated Foundation Coating

USES

AIM #410 Non-Fibrated Foundation Coating is recommended for commercial or residential foundations.

DESCRIPTION

AIM #410 Non-Fibrated Foundation Coating is a cold applied, non-fibrated, liquid asphalt in a solvent system ideal for damp- proofing above and below grade exterior concrete and masonry walls and foundations that are thoroughly dry.

APPLICATION:

FOR EXTERIOR USE ONLY. Surface must be clean and dry, and free of moisture both on and beneath the surface. Remove rust and scale from metal by wire brushing. Carefully inspect entire area to be coated. Repair all cracks, breaks, tears and holes. Stir coating thoroughly. Do not thin. Apply a single coat over the entire surface with a brush or heavy duty spray equipment.

PRECAUTIONS

In cold weather, store unopened container in a warm room overnight before using. DO NOT APPLY IF THERE IS A THREAT OF RAIN WITHIN 24 HOURS. Avoid contact with coating after it is applied. Over-application, especially in cold weather, may cause sagging. Exposed coating tends to soften in warm weather. Do not heat container or store at temperatures greater than 110°F. **COVERAGE:** 1.5 to 2.0 gallons per 100 square feet. Do not over-apply.

CLEAN UP: Remove coating from tools, etc., with paint thinner or mineral spirits. Clean hands with a waterless hand cleaner. Use care when handling solvents.

CAUTION

COMBUSTIBLE LIQUID AND VAPOR

Contains petroleum distillate. Harmful or fatal if swallowed. Vapor harmful. May affect the brain or central nervous system causing dizziness, headache, or nausea. Causes nose and throat irritation. Causes eye irritation. Causes skin irritation. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

Keep away from heat and open flame. Use only with adequate ventilation. Do not breathe vapors. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.

First Aid: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

Warning: This product contains a chemical known to the State of California to cause cancer.

SPECIFICATIONS

Appearance	Black, Smooth gloss	Maximum VOC	250 g/l
Base asphalt	Refined	Maximum VOS	2.10 lbs/gal
Brookfield Viscosity	2000-4000 cPs	Solids by Weight	74% minimum
Consistency @ 77° F	Brush, Spray	Specific Gravity @ 77° F (25°C)	0.93
Drying Time @ 50% R.H.	8 hrs set to	Weight per Gallon	7.6- 8.2 lbs
touch 68°F (20°C)		(ASTMD-1475)	
Flash Point	105° F		
(ASTMD-3278)			



LIMITED WARRANTY

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of 12 months from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application.

LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.



6505 West Park Boulevard • Suite 306-366 • Plano, TX 75093 • (214) 254-4720