



PRODUCT DATA SHEET

#820 Terpolymer Gutter Sealant

USES

AIM #820 Terpolymer Gutter Sealant is a multipurpose, nitrile elastomer based self-leveling sealant. Specifically designed as a narrow seam sealant for gutter lap joints on new gutter installations. Low modulus and high elongation accommodate severe movement. Excellent adhesion to metal gutters. For a non-sag, clear sealant, or for a gutter repair sealant, please refer to AIM #820 Terpolymer Gutter Sealant. Standard color is Aluminum.

APPLICATION

Surface to be sealed must be clean. To use, cut tip to size and puncture seal. Maximum recommended joint width is 1/8 inch. Apply two 1/8 inch beads to the edge of the gutter lap and slide the two pieces together to ensure full contact. Apply a second 1/8 inch bead to the lap seam on the interior of the gutter. May be painted. For outdoor use only. Some paints may require up to one week cure time before application. Keep unopened container warm prior to use.

CAUTION

COMBUSTIBLE LIQUID AND VAPOR

Contains petroleum distillate. Harmful or fatal if swallowed.

Vapor harmful. May affect the brain or central nervous system causing dizziness, headache, or nausea. Causes nose and throat irritation. Causes eye irritation. Causes skin irritation. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

Keep away from heat and open flame. Use only with adequate ventilation. Do not breathe vapors. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.

First Aid: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

Warning: This product contains a chemical known to the State of California to cause cancer.

SPECIFICATIONS

Recommended rate of application	See Application	Flash Point (TCC)	-4°F (-20°C)
% Solids by Weight	40 min	Container Sizes	10 oz. caulk tubes
Elongation ASTM D-412	1200% min @ 77°F (25°C)	Standard Color:	Aluminum
Tensile Strength	300 PSI		
VOC	<4% or 40 g/l		
(compliant in all 50 states)			

LIMITED WARRANTY

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.



Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of 12 months from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application.

LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.



6505 West Park Boulevard • Suite 306-366 • Plano, TX 75093 • (214) 254-4720