



# PRODUCT DATA SHEET

## #950 Asphaltic Driveway Sealer

### USES

AIM 950 Asphaltic Driveway Sealer is an oil-based asphalt pavement sealer designed to fill hairline cracks, beautify asphalt surfaces and rejuvenated dried-out asphalt surfaces (Contains Gilsonite). Does not contain water.

### DESCRIPTION

AIM 950 Asphaltic Driveway Sealer is an oil-based driveway sealer that penetrates and rejuvenates dried out asphalt surfaces and seals hairline cracks. Provides a black protective finish, which helps eliminate water penetration and prevent freeze/thaw cracking. Dries to a rich glossy black finish while protecting the pavement binder from oxidation damage.

**PREPARATION:** The surface should be clean and dry. Oil and grease spots should be scrubbed with driveway cleaner, strong household or dishwashing detergent. Flush the area with clean water and allow to dry before sealing. Cracks wider than hairline should be filled with asphalt crack filler or blacktop patch. Allow filled cracks to dry prior to sealing.

**APPLICATION:** Apply coating with brush, squeegee or medium nap roller. Spread evenly, working sealer into driveway pores. Apply coating as thin as possible and do not allow puddling in low areas. Final brush strokes should be in one direction for best results. Clean up with mineral spirits or waterless hand cleaner. Use care when handling solvents.

**COVERAGE:** Unsealed driveways – 75 sq.ft./gallon; previously sealed – 100 sq.ft./gal. Recommended coverage rates should be followed as close as possible. Over application may cause surface to become slippery.

**DRY TIME:** Under normal conditions the sealer will dry to the touch in 1-2 hours and may be opened to traffic in 24 hours. Application at higher than recommended coverage rates can dramatically increase drying times.

### FOR BEST RESULTS:

Do NOT use on driveways less than 1 year old.

Do NOT apply on driveways previously sealed with Coal Tar Emulsion. \*Best results are achieved when applied at temperatures below 80°F. Hot and humid days can cause the top surface of the sealer to prematurely dry. This may lead to re-emulsification and browning. In the case of browning, gently wash the surface with a solution of T.S.P. (Tri Sodium Phosphate) and water. Then rinse the driveway with clean tap water. If the sealer must be applied on extremely hot days, plan your work to begin early in the morning or evening when the driveway temperature is lower.

### SPECIFICATIONS:

Flash Point	105 F min.
Weight per gallon	7.4 lbs.
Non-volatile.	60% min.
% of specially compounded bitumen	58% min.
% of total solids by volume	64% min.
Film thickness	4-5 mils
Drying time	12-24 hours
Resistance to oils & solvents	Poor
Resistance to chemicals	Good
Resistance to Sunlight	Good
Effect of weathering	Slow Erosion
Water resistance under good drainage conditions	Excellent
Water resistance under Continuous submersion	Fair
Packaging	5-gallon pails

### CAUTION

#### COMBUSTIBLE LIQUID AND VAPOR

Contains petroleum distillate. Harmful or fatal if swallowed.

Vapor harmful. May affect the brain or central nervous system causing dizziness, headache, or nausea. Causes nose and throat irritation. Causes eye irritation. Causes skin irritation. Reports have associated repeated and prolonged occupational



exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Keep away from heat and open flame. Use only with adequate ventilation. Do not breathe vapors. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

**KEEP OUT OF REACH OF CHILDREN.**

**First Aid:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

**WARNING:** This product contains a chemical known to the State of California to cause cancer.

**LIMITED WARRANTY**

**TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.**

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of 12 months from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application.

**LIMITATION OF LIABILITY:** In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

