



PRODUCT DATA SHEET

#980 Polymer Modified Driveway Sealer-Filler

USES

AIM #980 Polymer Modified Driveway Sealer Filler is designed to protect and beautify sound asphalt surfaces, fill hairline cracks and provide increased traction. Blended from the high quality refined asphalt, AIM #980 Polymer Modified Driveway Sealer Filler promotes longer life and early wash-off resistance and Easy Stirring. This product contains no harmful solvents and is free of the irritating odors associated with Coal Tar sealers. AIM #980 Polymer Modified Driveway Sealer Filler will provide a tough, durable rich black finish, which is resistant to tracking.

PREPARATION

1. **CLEAN** surface to be coated. Sweep off all loose dirt, dust and debris. Scrub grease and oil spots with an all-purpose detergent. Flush cleaned area with garden hose using strong water pressure.
2. **REPAIR** all cracks and potholes larger than 1/8". Cracks smaller than 1/2" may be repaired using AIM #910 Driveway Crack Filler Pour Grade. Larger cracks, holes and depressions should be repaired using AIM #920 Driveway Crack Filler Trowel Grade or AIM #940 Pothole Patch. Allow repaired areas to properly cure before sealing.

APPLICATION:

1. **STIR** slightly to assure uniformity. AIM #980 Polymer Modified Driveway Sealer Filler is designed to eliminate any hard-packed settling. Little stirring is required. Do not thin.
2. **LIGHTLY DAMPEN** the surface with water when applied in temperature above 80 degrees. Surface may be damp during application but puddles of water should be avoided.
3. **APPLY** sealer with a roller or long handled Driveway Applicator, (squeegee on one side and brush on the other), at a rate of 1 gallon per 100 square feet. To assure proper coverage, measure out 1 gallon of sealer and apply to a premeasured area of 100 square feet (10 ft. X 10 ft.). Spread sealer evenly and thinly with the squeegee part of applicator. Use the brush end of applicator to work sealer into rough areas and remove excess sealer from low areas.
4. **FINISH** the area with a light pass of the brush assuring that all finishing strikes are in one direction for best appearance. Using the above application rate, continue to pour, spread and brush the sealer over the remaining surface.

COVERAGE: 100 square feet per gallon for smooth or previously sealed surfaces (500 sq.ft. /5 gal.). Rough, porous or previously unsealed driveways may require slightly more.

CLEAN UP: Soap and water can be used to clean tools before this product dries. Dried material may be cleaned up with mineral spirits or waterless hand cleaner. Use care when handling solvents.

HELPFUL HINTS & PRECAUTIONS

- This product will cure in 4 hours for light vehicle traffic when applied according to labeled instructions. Temperatures below 65° F and relative humidity above 60% will increase the cure time.
- Avoid parking vehicles on coated surface for 24 hours.
- Apply coating in the morning on a clear sunny day with temperatures at or above 65 °F. This will allow the coating the benefit of the full day's sunshine.
- The old adage "more is better" does not apply to driveway sealers. Recommended coverage rates should be followed as close as possible. Over application can dramatically increase cure time, tracking and may cause the surface to become slippery.
- Allow new driveways a period of 6 months to cure before sealing.
- Do not apply to concrete.

KEEP FROM FREEZING

CAUTION

Do not take internally. Avoid prolonged contact with skin or fumes. If irritation occurs seek medical attention. If swallowed, do not induce vomiting.

KEEP OUT OF REACH OF CHILDREN.



First Aid: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

Warning: This product contains a chemical known to the State of California to cause cancer.

Container sizes 5, 55 gal

LIMITED WARRANTY

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of 12 months from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application.

LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.



6505 West Park Boulevard • Suite 306-366 • Plano, TX 75093 • (214) 254-4720