



SAFETY DATA SHEET

This safety data sheet complies with the requirements of: 29CFR1910.1200

Issue Date 21-Oct-2015

Revision Date 21-Oct-2015

Version 1

Product identifier

Product Name Clear Sealant - Non Fibrated

Other means of identification

Product Code AIM 870

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant.

Uses advised against For exterior use only. Do not use indoors.

Details of the supplier of the safety data sheet

Manufacturer Address American Industrial Manufacturers of Building Materials
6505 W Park Blvd
Suite 306-366
Plano, Texas 75093
(214) 254-4720

Emergency telephone number

Emergency Telephone Call CHEMTREC Day or Night:
Within USA and Canada: 1-800 424-9300
Outside USA and Canada: 1-703-527-3887

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 3

Label elements

Emergency Overview

Danger

Hazard statements

Causes damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Flammable liquid and vapor



Appearance Viscous	Physical state Liquid	Odor Solvent (Mineral Spirits)
---------------------------	------------------------------	---------------------------------------

Precautionary Statements - Prevention

Do not breathe dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed when product is not in use.
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Get medical advice/attention if you feel unwell
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting
In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Disposal should be in accordance with applicable local, regional, national and international laws and regulations.

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- May be harmful in contact with skin
- Causes mild skin irritation
- Toxic to aquatic life with long lasting effects
- Harmful to aquatic life

Unknown acute toxicity 45% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance**Mixture**

This product is a mixture.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Common name	Sealant and Caulk.
Synonyms	None.
Chemical nature	Organic solvents and additives.

Chemical Name	CAS No.	Weight-%	Trade Secret
Mineral Spirits (with < 0.1% Benzene)	8052-41-3	20 - 30%	*
Aromatic Naptha (with <0.1% Benzene)	64742-95-6	20 - 30%	*
Hydrocarbon Resin	69430-35-9	10 - 20%	*
Styrene/Butadiene Copolymer	66070-58-4	10 - 20%	*
1,2,4 Trimethylbenzene	95-63-6	0 - 10%	*

4. FIRST AID MEASURES

Description of first aid measures

General advice	Contains petroleum distillate. Harmful or fatal if swallowed. Vapor harmful. May affect the brain or central nervous system causing dizziness, headache, or nausea. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
Eye contact	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin contact	Wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. In the case of skin irritation or allergic reactions see a physician.
Inhalation	Move to fresh air in case of accidental inhalation of vapors. If continued difficulty with breathing is experienced, get medical attention immediately.
Ingestion	Not an expected route of exposure. If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	First aider: Pay attention to self-protection!.

Most important symptoms and effects, both acute and delayed

Symptoms May cause skin irritation. May cause eye irritation.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO₂). Sand. Use foam or water FOG as a last resort.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Sealed container may rupture/burst when heated or exposed to excessive heat.

Hazardous combustion products Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

Explosion data

Sensitivity to Mechanical Impact Not sensitive.

Sensitivity to Static Discharge May be ignited by heat, sparks or flames.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions No action should be taken involving any personal risk or without suitable training. Use personal protective equipment as required.

Other Information Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area).

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent product from entering sewers, drains, or waterways. Local authorities should be advised if significant spillages can not be contained. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Contain spillage with non-combustible absorbent material, e.g. sand, earth, diatomaceous earth, vermiculite.

Methods for cleaning up Pick up the absorbed material (described just above) and transfer to properly labeled containers for disposal according to local / national regulations (see Section 13).

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use personal protective equipment as required. Remove all sources of ignition. Use only outdoors.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, dry, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition.

Incompatible materials Strong acids. Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines No ACGIH or OSHA PEL is assigned to this mixture. Exposure limits for the component materials are shown below. This product, as supplied, is not believed to contain any hazardous material that exceeds exposure limits established by OSHA. .

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Mineral Spirits (with < 0.1% Benzene) 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
1,2,4 Trimethylbenzene 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m ³

Appropriate engineering controls

Engineering Controls Use natural cross ventilation, local (mechanical) pick-up, and/or general area mechanical cross ventilation. Ventilation pattern should be designed to prevent accumulation of asphalt vapors. Ventilation must be sufficient to maintain asphalt vapor concentrations below the TWA limits outlined above.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing that is resistant to chemical penetration.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, a NIOSH/MSHA approved respiratory protection should be worn.

General Hygiene Considerations Wash face, hands and any exposed skin thoroughly after handling. Wash contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	Odor	Solvent (Mineral Spirits)
Appearance	Viscous	Odor threshold	1-30 PPM. Odor thresholds vary greatly. Do not rely on odor threshold alone to determine potentially hazardous substances.
Color	White		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not applicable	
Melting point/freezing point	None / -70 °C None / -94 °F	Melting Point is not applicable. Freezing points are shown.
Boiling point / boiling range	> 154 °C / 310 °F	
Flash point	> 40.5 °C / > 105 °F	Setaflash
Evaporation rate	0.1	Butly acetate = 1
Flammability (solid, gas)	No information available	
Flammability Limit in Air		Flammable above 105 degrees F and 40.5 degrees C.
Upper flammability limit:	7.0	
Lower flammability limit:	1.6	
Vapor pressure	0.3 (kPa)	@ 20 °C
Vapor density	5.3	Where: Air = 1 at 68 degrees F (20 degrees C)
Specific Gravity	1.10	Water = 1g/ml
Water solubility	Insoluble	
Solubility in other solvents	Soluble in aromatic and aliphatic solvents.	
Partition coefficient	No information available	No data available.
Autoignition temperature	330 °C / 626 °F	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	Vapor accumulation could flash or explode if ignited.	
Oxidizing properties	None	

Other Information

Softening point	Not applicable
Molecular weight	No information available
VOC Content (%)	Less than 550 g/l.
Density	9.0 to 9.4 10lb/gal
Bulk density	Not applicable

10. STABILITY AND REACTIVITY

<u>Reactivity</u>	
Not applicable	Not applicable

Chemical stability

Stable.

Possibility of Hazardous Reactions

None under normal use.

Hazardous polymerization	Hazardous polymerization does not occur.
---------------------------------	--

Conditions to avoid

Avoid static discharge. Avoid heat, sparks, and open flame.

Incompatible materials

Strong acids. Strong oxidizing agents.

Hazardous Decomposition Products

Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.
Inhalation	Avoid breathing vapors or mists.
Eye contact	Avoid contact with eyes. Contact with eyes may cause irritation.
Skin contact	May cause irritation.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately. Not an expected route of exposure.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Aromatic Naptha (with <0.1% Benzene) 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
1,2,4 Trimethylbenzene 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h

Information on toxicological effects

Symptoms	Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
-----------------	--

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Can cause skin irritation.
Serious eye damage/eye irritation	Irritating to eyes.
Irritation	Irritating to eyes, respiratory system and skin.
Corrosivity	Not classified.
Sensitization	May cause sensitization of susceptible persons.
Germ cell mutagenicity	This product does not contain any ingredients that cause germ cell mutagenicity.
Carcinogenicity	This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.
Legend	
Reproductive toxicity	None known for product as a whole.
Developmental Toxicity	None known for product as a whole.
Teratogenicity	None known.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration hazard	No information available.

Numerical measures of toxicity - No information available

The following values are calculated based on chapter 3.1 of the GHS document For exterior use only. Do not use indoors.

ATEmix (oral)	10,444.00
ATEmix (dermal)	3,976.00
ATEmix (inhalation-dust/mist)	9.17

12. ECOLOGICAL INFORMATION

Ecotoxicity

The following table lists information related to aquatic toxicity

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Aromatic Naptha (with <0.1% Benzene) 64742-95-6	-	9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
1,2,4 Trimethylbenzene 95-63-6	-	7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
1,2,4 Trimethylbenzene 95-63-6	3.63

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods**Disposal of wastes**

Disposal should be in accordance with applicable local, regional, national and international laws and regulations.

Contaminated packaging

Do not reuse container.

14. TRANSPORT INFORMATION

DOT

Proper shipping name Flammable Liquid, n.o.s. (Petroleum Distillates)
Hazard Class 3
Packing Group III

TDG

UN/ID no. Regulated
 NA 1993
Proper shipping name Flammable Liquid, n.o.s. (Petroleum Distillates)
Hazard Class 3
Packing Group III

MEX

Regulated

ICAO (air)

Regulated

IATA

Regulated

IMDG

Regulated

RID

Not applicable in the United States.

ADR

Not applicable in the United States.

ADN

Not applicable in the United States.

15. REGULATORY INFORMATION

International Inventories

TSCA All of the components of this product are listed on the US TSCA (Toxic Substances Control Act) Inventory or are exempt.

DSL/NDSL All of the components of this product are listed on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
1,2,4 Trimethylbenzene - 95-63-6	1.0

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

This product contains the following substances regulated by various State Right-to-Know regulations.

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Mineral Spirits (with < 0.1% Benzene) 8052-41-3	X	X	X
1,2,4 Trimethylbenzene 95-63-6	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 2	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2	Flammability 2	Physical hazards 0	Personal protection -
Chronic Hazard Star Legend		* = Chronic Health Hazard		

Prepared By AIM Administrative Services Department
Issue Date 21-Oct-2015
Revision Date 21-Oct-2015

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet