



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Complies with OSHA GHS Revision 7 of 2024.

Issuing Date 13-Nov-2024

Revision Date 13-Nov-2024

Version 1

1. Identification

Product identifier

Product Name Non-Fibrated Roof Coating

Other means of identification

Product Code AIM 200

Synonyms SEALANT

Recommended use of the chemical and restrictions on use

Recommended Use Roof Coating An economical means of recoating and preserving smooth-surface asphalt roofs.

Restrictions on use For exterior use only. Do not use indoors. This product is not intended for use over tar or asphalt and gravel roofs.

Details of the supplier of the safety data sheet

Supplier Address

American Industrial Manufacturers of Building Materials
W. Park Blvd
Suite 306-366
Plano, Texas 75093
(214) 254-4720

Emergency telephone number

Company Phone Number (214) 254-4720

Emergency Telephone Call CHEMTREC Day or Night:
Within USA and Canada: 1-800 424-9300
Outside USA and Canada: 1-703-527-3887

2. Hazard(s) identification

Classification

Flammable liquids	Category 3
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2B
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration hazard	Category 1

Hazards not otherwise classified (HNOC)

Not applicable.

Label elements

Danger

Hazard statements

Flammable liquid and vapor.
Causes skin irritation.
Causes eye irritation.
Suspected of causing cancer.
May cause respiratory irritation. May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.

Precautionary Statements - Prevention

Do not handle until all safety precautions have been read and understood.
Wear protective gloves/clothing and eye/face protection.
Wash face, hands and any exposed skin thoroughly after handling.
Do not breathe dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
If skin irritation occurs: Get medical advice/attention.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
Wash contaminated clothing before reuse.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF SWALLOWED: Immediately call a POISON CENTER or doctor.
Do NOT induce vomiting.
In case of fire: Use CO₂, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed.

Precautionary Statements - Disposal

Disposal should be in accordance with applicable local, regional, and national laws and regulations..

Other Information

May be harmful in contact with skin.

3. Composition/information on ingredients**Substance**

Not applicable.

Mixture

Common name Asphalt Roof Coating.

Synonyms SEALANT.

Chemical nature Organic solvents and additives.

Chemical name	CAS No.	Weight-%	Trade secret
Asphalt (at Ambient Temperature)	8052-42-4	70-80	*
Mineral Spirits (with < 0.1% Benzene)	8052-41-3	15-25	*
Nonane	111-84-2	1-5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice	IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
Effects of Exposure	May cause damage to organs through prolonged or repeated exposure.

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
---------------------------	------------------------

5. Fire-fighting measures

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition.
Hazardous combustion products	Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.
--------------------------------	---

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep out of the reach of children.
---------------------------	--

8. Exposure controls/personal protection

Control parameters**Exposure Limits**

No ACGIH or OSHA PEL is assigned to this mixture.
This product, as supplied, is not believed to contain any hazardous material that exceeds exposure limits established by OSHA.

Exposure limits for the component materials are shown below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Asphalt (at Ambient Temperature) 8052-42-4	TWA: 0.5 mg/m ³ Benzene-soluble aerosol fume, inhalable particulate matter	-	Ceiling: 5 mg/m ³ fume 15 min
Mineral Spirits (with < 0.1% Benzene) 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
Nonane 111-84-2	TWA: 200 ppm	(vacated) TWA: 200 ppm (vacated) TWA: 1050 mg/m ³	TWA: 200 ppm TWA: 1050 mg/m ³

Biological occupational exposure limits

Chemical name	ACGIH
Asphalt (at Ambient Temperature) 8052-42-4	2.5 µg/L - urine (1-Hydroxypyrene with hydrolysis) - end of shift at end of workweek

Appropriate engineering controls

Engineering controls None under normal use conditions.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes.

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

9. Physical and chemical properties**Information on basic physical and chemical properties**

Physical state	Liquid
Appearance	Viscous
Color	Black
Odor	Solvent (Mineral Spirits)
Odor threshold	1-30 PPM. Odor thresholds vary greatly. Do not rely on odor threshold alone to determine potentially hazardous substances.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not applicable	7.0
pH (as aqueous solution)		None known
Melting point/freezing point	None / -70 None / -94	Melting Point is not applicable. Freezing points are shown.
Boiling point / boiling range	> 154 °C / 309.2 °F	
Flash point	> 40.5 °C / 104.90 °F	Setaflash
Evaporation rate	0.1	Butly acetate = 1
Flammability (solid, gas)		
Flammability Limit in Air		Flammable above 105 degrees F and 40.5 degrees C.
Upper flammability limit:	7.0	
Lower flammability limit:	1.6	
Vapor pressure	0.3 (kPa)	@ 20 °C
Vapor density	5.3	Where: Air = 1 at 68 degrees F (20 degrees C)
Relative density	0.95	Water = 1g/ml
Water solubility	No data available Insoluble	Reacts with water to form carbon dioxide
Solubility(ies)	No data available.	Insoluable
Partition coefficient	No data available.	No data available.
Autoignition temperature	330 °C / 626 °F	
Decomposition temperature		
Kinematic viscosity		
Dynamic viscosity	No data available.	@ 25 °C
<u>Other information</u>		
Explosive properties	No information available	
Oxidizing properties	No information available	
Softening point	Not applicable	
Molecular weight	N/A	
VOC Content (%)	Less than 270 g/l.	
Density	7.8 to 8.1 lb/gal	
Bulk density	Not applicable	

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Hazardous polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong acids. Strong bases. Strong oxidizing agents.
Hazardous decomposition products	Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation. Causes

eye irritation. May cause redness, itching, and pain.

Skin contact

Specific test data for the substance or mixture is not available. Repeated exposure may cause skin dryness or cracking. Causes skin irritation.

Ingestion

Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics**Symptoms**

Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity**Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	5,046.70 mg/kg
ATEmix (dermal)	2,018.70 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-vapor)	27.50 mg/l
ATEmix (inhalation-dust/mist)	99,999.00 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Asphalt (at Ambient Temperature) 8052-42-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 94.4 mg/m ³ (Rat) 4.5 h
Mineral Spirits (with < 0.1% Benzene) 8052-41-3	-	> 3000 mg/kg (Rabbit)	> 5.5 mg/L (Rat) 4 h
Nonane 111-84-2	-	-	= 3200 ppm (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Skin corrosion/irritation**

Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation

Classification based on data available for ingredients. Causes eye irritation.

Respiratory or skin sensitization

No information available.

Germ cell mutagenicity

No information available.

Carcinogenicity

Contains a known or suspected carcinogen. Classification based on data available for ingredients. Suspected of causing cancer.

Reproductive toxicity

No information available.

Developmental Toxicity

None known for product as a whole.

Teratogenicity	None known.
STOT - single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Target organ effects	Kidney, Respiratory system, Eyes, Skin, Central nervous system.
Aspiration hazard	May be fatal if swallowed and enters airways.
Other adverse effects	N/A.
Interactive effects	No information available.

12. Ecological information

Ecotoxicity	Toxicological testing has not been performed for this product overall. Available toxicological data for individual ingredients is summarized below.
Persistence and degradability	N/A.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Asphalt (at Ambient Temperature) 8052-42-4	6

Other adverse effects	No information available.
-----------------------	---------------------------

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

14. Transport information

<u>DOT</u>	Regulated DOT Ground: Not regulated if containers are less than 119 gallons (450 liters). DOT Ground: Regulated if shipped in containers >119 gallons (450 liters).
Proper shipping name Hazard Class	Combustible liquid, n.o.s (mineral spirits) 3

Packing Group III

TDG

UN/ID no. NA 1993
 Proper shipping name Combustible liquid, n.o.s (mineral spirits)
 Hazard Class 3
 Packing Group III

MEX

UN/ID no. Regulated
 NA 1993
 Proper shipping name Combustible liquid, n.o.s. (mineral spirits)

ICAO (air)

UN/ID no. Regulated
 1993

IATA

UN number or ID number Regulated
 1993

IMDG

UN number or ID number Regulated
 1993

15. Regulatory information

International Inventories**TSCA**

All of the components of this product are listed on the US TSCA (Toxic Substances Control Act) Inventory or are exempt.

Chemical name	CAS No.	Inventory Listing Status	Commercial Activity Designation
Asphalt (at Ambient Temperature)	8052-42-4	Present	Active
Mineral Spirits (with < 0.1% Benzene)	8052-41-3	Present	Active
Nonane	111-84-2	Present	Active
Trimethyl Benzene (mixed Isomers)	25551-13-7	Present	Active

DSL/NDSL

All of the components of this product are listed on the DSL.

EINECS/ELINCS

All components are listed.

TCSI

Contact supplier for inventory compliance status.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

TCSI - Taiwan Chemical Substance Inventory

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Asphalt (at Ambient Temperature) 8052-42-4	X	X	X
Mineral Spirits (with < 0.1% Benzene) 8052-41-3	X	X	X
Nonane 111-84-2	X	X	X
Trimethyl Benzene (mixed Isomers) 25551-13-7	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA	Health hazards 2	Flammability 2	Instability 0	Special hazards -
HMIS	Health hazards 2 *	Flammability 2	Physical hazards 0	Personal protection -
<i>Chronic Hazard Star Legend * = Chronic Health Hazard</i>				

Key or legend to abbreviations and acronyms used in the safety data sheet**Legend**

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
STOT: Specific Target Organ Toxicity
ATE: Acute Toxicity Estimate
LC50: 50% Lethal Concentration
LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
+	Sensitizers		

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGL(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Prepared By	AIM Administrative Services Department.
Issuing Date	13-Nov-2024
Revision Date	13-Nov-2024
Revision Note	Revised to comply with OSHA GHS Revision 7 of 2024.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.