



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Complies with OSHA GHS Revision 7 of 2024.

Issuing Date 21-Jan-2025

Revision Date 21-Jan-2025

Version 1

1. Identification

Product identifier

Product Name Acrylic Sealant

Other means of identification

Product Code AIM 840

Synonyms SEALANT

Recommended use of the chemical and restrictions on use

Recommended Use White acrylic mastic used to repair roofs and seal metal roof fasteners prior to coating with white elastomeric roof coatings

Restrictions on use For exterior use only. Do not use indoors.

Details of the supplier of the safety data sheet

Supplier Address

American Industrial Manufacturers of Building Materials
W. Park Blvd
Suite 306-366
Plano, Texas 75093
(214) 254-4720

Emergency telephone number

Company Phone Number (214) 254-4720

Emergency Telephone Call CHEMTREC Day or Night:
Within USA and Canada: 1-800 424-9300
Outside USA and Canada: 1-703-527-3887

2. Hazard(s) identification

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2B
Carcinogenicity	Category 1A

Hazards not otherwise classified (HNOC)

Not applicable.

Label elements



Danger

Hazard statements

Causes skin irritation.
Causes eye irritation.
May cause cancer.

Precautionary Statements - Prevention

Do not handle until all safety precautions have been read and understood.
Wash face, hands and any exposed skin thoroughly after handling.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF ON SKIN: Wash with plenty of water and soap.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
Get medical help if you feel unwell.
Rinse mouth.

Precautionary Statements - Storage

Keep From Freezing.

Precautionary Statements - Disposal

Disposal should be in accordance with applicable local, regional, and national laws and regulations..

Other Information

No information available.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Common name Acrylic White Mastic.
Synonyms SEALANT.
Chemical nature Mixture of moisture reactive polymers, plasticizers and fillers.

Chemical name	CAS No.	Weight-%	Trade secret
Calcium Carbonate	1317-65-3	10-15	*
Titanium Dioxide	13463-67-7	1-5	*
Quartz	14808-60-7	0.1=0.3	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice	IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.
Inhalation	No hazards which require special first aid measures.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Consult a physician if necessary. Not an expected route of exposure.
Self-protection of the first aider	Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms	No information available.
Effects of Exposure	No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
---------------------------	------------------------

5. Fire-fighting measures

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	No information available.
Hazardous combustion products	Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.
Special protective equipment and precautions for fire-fighters	Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with skin, eyes or clothing.
-----------------------------	--

Methods and material for containment and cleaning up

- Methods for containment** Prevent further leakage or spillage if safe to do so.
- Methods for cleaning up** Pick up and transfer to properly labeled containers.
- Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep from freezing.

8. Exposure controls/personal protection

Control parameters

Exposure Limits No ACGIH or OSHA PEL is assigned to this mixture.
 This product, as supplied, is not believed to contain any hazardous material that exceeds exposure limits established by OSHA.

Exposure limits for the component materials are shown below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Calcium Carbonate 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Titanium Dioxide 13463-67-7	TWA: 0.2 mg/m ³ nanoscale respirable particulate matter TWA: 2.5 mg/m ³ finescale respirable particulate matter	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³ TWA: 2.4 mg/m ³ CIB 63 fine TWA: 0.3 mg/m ³ CIB 63 ultrafine, including engineered nanoscale
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

		TWA respirable fraction	
--	--	-------------------------	--

Appropriate engineering controls

Engineering controls None under normal use conditions.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes.

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid
Appearance Viscous
Color White
Odor Low
Odor threshold Negligible odor.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not applicable	7.0
pH (as aqueous solution)		None known
Melting point/freezing point	None / 0 None / 32	Melting Point is not applicable. Freezing points are shown.
Boiling point / boiling range	> 100 °C / 212 °F	
Flash point	Not applicable	Non Flammable
Evaporation rate	The evaporation rate of the water component of this emulsion product is dependent upon: 1) The temperature of the water at the air-water surface; 2) The humidity of the air; 3) The area of the air-water surface; 4) The temperature of the air.	No data available. Evaporation rate is dependent upon atmospheric conditions.
Flammability (solid, gas)	Non Flammable	
Flammability Limit in Air		Not flammable
Upper flammability limit:	Not applicable	
Lower flammability limit:	Not applicable	
Vapor pressure	2.33 (kPa)	@ 20 °C
Vapor density	5.3	Where: Air = 1 at 68 degrees F (20 degrees C)
Relative density	1.34	Water = 1g/ml
Water solubility	No data available Dispersible	Reacts with water to form carbon dioxide
Solubility(ies)	No data available.	Insoluable
Partition coefficient	No data available.	No data available.
Autoignition temperature	330 °C / 626 °F	
Decomposition temperature		
Kinematic viscosity		
Dynamic viscosity	No data available.	@ 25 °C

Other information

Explosive properties	No information available
Oxidizing properties	No information available
Softening point	Not applicable
Molecular weight	N/A
VOC Content (%)	Less than 50 g/l
Density	11.0 to 11.4 lb/gal
Bulk density	Not applicable

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Hazardous polymerization	Hazardous polymerization does not occur.
Conditions to avoid	None known based on information supplied.
Incompatible materials	Strong acids. Strong bases. Strong oxidizing agents.
Hazardous decomposition products	Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.

11. Toxicological information**Information on likely routes of exposure**

Product Information	<p>The IARC Monograph (Vol 93, 2010, Carbon Black, Titanium Dioxide, Talc) states: Operators in user industries who handle fluffy or pelleted Carbon Black during rubber, paint and ink production are expected to have significantly lower exposures to Carbon Black than workers in Carbon Black production. Other workers in user industries who handle it occasionally have little opportunity for exposure. And further... "End-users of these products (rubber, ink or paint) are unlikely to be exposed to airborne Carbon Black particles, which are bound within the product matrix."</p> <p>Based upon the screening level assessment using testing data submitted by NPCA on the amounts of respirable silica produced from the normal use of interior flat latex paints, OEHHA has decided to issue a safe use determination to NPCA for crystalline silica (quartz) in interior latex paints.</p> <p>The same method of encapsulation, as used for latex paints, is used for this product. Therefore, the crystalline silica (quartz) that is used in this product is not considered hazardous.</p>
Inhalation	Specific test data for the substance or mixture is not available.
Eye contact	Specific test data for the substance or mixture is not available.
Skin contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Redness. May cause redness and tearing of the eyes.
-----------------	---

Acute toxicity**Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	8,719.90 mg/kg
ATEmix (dermal)	9,173.00 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-vapor)	99,999.00 mg/l
ATEmix (inhalation-dust/mist)	28.80 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium Dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	= 5.09 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes eye irritation.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Titanium Dioxide 13463-67-7	A3	Group 2B	-	X
Quartz 14808-60-7	A2	Group 1	Known	X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

Occupational Safety and Health Administration of the US Department of Labor

X - Present

Reproductive toxicity No information available.

Developmental Toxicity None known for product as a whole.

Teratogenicity None known.

STOT - single exposure No information available.

STOT - repeated exposure	No information available.
Target organ effects	Respiratory system, Eyes, Skin, Lungs.
Aspiration hazard	No information available.
Other adverse effects	N/A.
Interactive effects	No information available.

12. Ecological information

Ecotoxicity	Toxicological testing has not been performed for this product overall. Available toxicological data for individual ingredients is summarized below.
Persistence and degradability	N/A.
Bioaccumulation	There is no data for this product.
Other adverse effects	No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Do not reuse empty containers.

14. Transport information

Note: This material is not subject to regulation as a hazardous material for shipping

DOT	Not regulated.
Hazard Class	3
Packing Group	III

IMDG Regulated

15. Regulatory information

International Inventories

TSCA All of the components of this product are listed on the US TSCA (Toxic Substances Control

Act) Inventory or are exempt.

Chemical name	CAS No.	Inventory Listing Status	Commercial Activity Designation
Styrene Acrylic Polymer Emulsion	25036-16-2	Present	Active
Water	7732-18-5	Present	Active
Calcium Carbonate	1317-65-3	Present	Active
Titanium Dioxide	13463-67-7	Present	Active
Amorphous Silica (Silicon Dioxide)	7631-86-9	Present	Active
Aluminum Hydroxide	21645-51-2	Present	Active
Quartz	14808-60-7	Present	Active

DSL/NDSL

All of the components of this product are listed on the DSL.

EINECS/ELINCS

All components are listed.

TCSI

Contact supplier for inventory compliance status.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

TCSI - Taiwan Chemical Substance Inventory

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
Titanium Dioxide - 13463-67-7	Carcinogen

Quartz - 14808-60-7	Carcinogen
---------------------	------------

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Water 7732-18-5	-	-	X
Calcium Carbonate 1317-65-3	X	X	X
Titanium Dioxide 13463-67-7	X	X	X
Diethylene glycol monobutyl ether 112-34-5	X	-	X
Amorphous Silica (Silicon Dioxide) 7631-86-9	-	X	X
Quartz 14808-60-7	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA Health hazards 2 Flammability 1 Instability 0 Special hazards -
HMIS Health hazards 2* Flammability 1 Physical hazards 0 Personal protection -
*Chronic Hazard Star Legend * = Chronic Health Hazard*

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
 PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
 vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
 STOT: Specific Target Organ Toxicity
 ATE: Acute Toxicity Estimate
 LC50: 50% Lethal Concentration
 LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)
 Ceiling Maximum limit value * Skin designation
 + Sensitizers

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
 U.S. Environmental Protection Agency ChemView Database
 European Food Safety Authority (EFSA)
 Environmental Protection Agency
 Acute Exposure Guideline Level(s) (AEGL(s))
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
 U.S. Environmental Protection Agency High Production Volume Chemicals
 Food Research Journal
 Hazardous Substance Database
 International Uniform Chemical Information Database (IUCLID)
 National Institute of Technology and Evaluation (NITE)
 Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
 NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Prepared By AIM Administrative Services Department.
Issuing Date 21-Jan-2025
Revision Date 21-Jan-2025
Revision Note Revised to comply with OSHA GHS Revision 7 of 2024.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.