

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Complies with OSHA GHS Revision 7 of 2024.

Issuing Date 21-Jan-2025 Revision Date 21-Jan-2025 Version 1

1. Identification

Product identifier

Product Name Driveway Crack Filler - Pour Grade

Other means of identification

Product Code AIM 910

Synonyms SEALANT

Recommended use of the chemical and restrictions on use

Recommended Use Used to fill cracks in asphalt and concrete joints, driveways and parking areas up to ½ inch

n width.

Restrictions on use For exterior use only. Do not use indoors.

Details of the supplier of the safety data sheet

Supplier Address

American Industrial Manufacturers of Building Materials W. Park Blvd Suite 306-366 Plano, Texas 75093 (214) 254-4720

Emergency telephone number

Company Phone Number (214) 254-4720

Emergency Telephone Call CHEMTREC Day or Night:

Within USA and Canada: 1-800 424-9300 Outside USA and Canada: 1-703-527-3887

2. Hazard(s) identification

Classification

Carcinogenicity	Category 1A	
Specific target organ toxicity (repeated exposure)	Category 1	

Hazards not otherwise classified (HNOC)

Not applicable.

Label elements



Danger

Hazard statements

May cause cancer.

Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements - Prevention

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash face, hands and any exposed skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Gently wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical help.

Call a POISON CENTER or doctor if you feel unwell.

Rinse mouth.

IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.

Precautionary Statements - Storage

Keep From Freezing.

Precautionary Statements - Disposal

Disposal should be in accordance with applicable local, regional, and national laws and regulations...

Other Information

No information available.

3. Composition/information on ingredients

Substance

Not applicable.

<u>Mixture</u>

Common name Driveway crack filler.

Synonyms SEALANT.

Chemical nature Mixture of moisture reactive polymers, plasticizers and fillers.

Chemical name	CAS No.	Weight-%	Trade secret
Asphalt (at Ambient Temperature)	8052-42-4	35-40	*
Kaolin	1332-58-7	5-10	*
Bentonite	1302-78-9	1-5	*
Quartz	14808-60-7	1-5	*
Titanium Dioxide	13463-67-7	0.2-0.5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice IF exposed or concerned: Get medical advice/attention.

Inhalation No hazards which require special first aid measures.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if symptoms occur.

Skin contact Wash skin with soap and water.

Ingestion Rinse mouth thoroughly with water. Get medical attention if symptoms occur. Not an

expected route of exposure.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Effects of Exposure May cause cancer.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

surrounding environment.

Unsuitable extinguishing mediaDo not scatter spilled material with high pressure water streams.

Specific hazards arising from the Non-comb

chemical

Non-combustible, substance itself does not burn but may decompose upon heating to

produce corrosive and/or toxic fumes.

Hazardous combustion products Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors

and fumes.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Non

Special protective equipment and precautions for fire-fighters

Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautionsNone under normal use conditions.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep from freezing.

8. Exposure controls/personal protection

Control parameters

Exposure Limits No ACGIH or OSHA PEL is assigned to this mixture.

This product, as supplied, is not believed to contain any hazardous material that exceeds

exposure limits established by OSHA.

Exposure limits for the component materials are shown below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH	1
Asphalt (at Ambient Temperature) 8052-42-4	TWA: 0.5 mg/m³ Benzene-soluble aerosol fume, inhalable particulate matter	-	Ceiling: 5 mg/m ³	fume 15 min
Kaolin 1332-58-7	TWA: 2 mg/m³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction (vacated) TWA: 10 mg/m³ total dust (vacated) TWA: 5 mg/m³ respirable fraction	TWA: 10 mg/m ³ TWA: 5 mg/m ³ dust	total dust respirable
Bentonite 1302-78-9	TWA: 1 mg/m³ respirable particulate matter	-	-	
Quartz 14808-60-7	TWA: 0.025 mg/m³ respirable particulate matter	TWA: 50 μg/m³ TWA: 50 μg/m³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m³ respirable dust : (250)/(%SiO2 + 5) mppcf TWA respirable fraction : (10)/(%SiO2 + 2) mg/m³	dust	

		TWA respirable fraction	
Titanium Dioxide	TWA: 0.2 mg/m ³ nanoscale	TWA: 15 mg/m ³ total dust	IDLH: 5000 mg/m ³
13463-67-7	respirable particulate matter	(vacated) TWA: 10 mg/m ³	TWA: 2.4 mg/m ³ CIB 63 fine
	TWA: 2.5 mg/m ³ finescale	total dust	TWA: 0.3 mg/m ³ CIB 63
	respirable particulate matter		ultrafine, including engineered
			nanoscale

Biological occupational exposure limits

Chemical name	ACGIH
Asphalt (at Ambient Temperature)	2.5 µg/L - urine (1-Hydroxypyrene with hydrolysis) - end of
	shift at end of workweek

Appropriate engineering controls

Engineering controls None under normal use conditions.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes.

Hand protection Wear suitable gloves.

Skin and body protectionWear suitable protective clothing.

exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and

immediately after handling the product.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical stateLiquidAppearanceViscousColorBlackOdorLow

Odor threshold Negligible odor.

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

PH Not applicable 7.0

pH (as aqueous solution)

None known

Melting point/freezing point None / 0 None / 32 Melting Point is not applicable. Freezing points are

shown.

Boiling point / boiling range > 100 °C / 212 °F

Flash point Non Flammable

Evaporation rateThe evaporation rate of the water

No data available. Evaporation rate is dependent

component of this emulsion product is upon atmospheric conditions.

dependent upon: 1) The temperature of the water at the air-water surface; 2) The humidity of the air; 3) The area of

the air-water surface; 4) The temperature of the air.

Flammability (solid, gas) Non Flammable

Flammability Limit in Air

Not flammable

Upper flammability limit: Not applicable

Revision Date 21-Jan-2025

Lower flammability limit: Not applicable

Vapor pressure 2.33 (kPa) @ 20 °C

Vapor density 5.3 Where: Air = 1 at 68 degrees F (20 degrees C)

Relative density 1.0 Water = 1g/ml

Water solubility

No data available Dispersible

Reacts with water to form carbon dioxide

Solubility(ies)No data available.InsoluablePartition coefficientNo data available.No data available.Autoignition temperature330 °C / 626 °F

Decomposition temperature

Kinematic viscosity

Dynamic viscosity No data available. @ 25 °C

Other information

Explosive properties No information available Oxidizing properties No information available

Softening point Not applicable

Molecular weight N/A

VOC Content (%)

Density

8.2 to 8.6 lb/gal

Bulk density

Not applicable

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions
None under normal processing.

Hazardous polymerization Hazardous polymerization does not occur.

Conditions to avoid None known based on information supplied.

Incompatible materialsNone known based on information supplied.

Hazardous decomposition products Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.

11. Toxicological information

Information on likely routes of exposure

Product Information

The IARC Monograph (Vol. 103, 2013, Bitumen and Bitumen Emissions) defines Asphalt as 'Group 2B, Possible Carcinogen to Humans'. This definition is based on studies of exposure to Asphalt fumes at elevated temperatures. The Monograph states that temperature plays an important role in determining the degree of exposure and also the carcinogenic potential of bitumen emissions. This same Monograph states that Asphalt is non volatile at ambient temperature. There is no data presented in the Monograph to demonstrate that Asphalt at ambient temperature is considered a carcinogen. Since the normal use of this product is at ambient temperature, the Asphalt used in this product is not listed as a carcinogen. No other national or international agency has defined Asphalt as a carcinogen.

The IARC Monograph (Vol 93, 2010, Carbon Black, Titanium Dioxide, Talc)

states:Operators in user industries who handle fluffy or pelleted Carbon Black during rubber, paint and ink production are expected to have significantly lower exposures to Carbon Black than workers in Carbon Black production. Other workers in user industries who handle it occasionally have little opportunity for exposure. And further... "End-users of these products (rubber, ink or paint) are unlikely to be exposed to airborne Carbon Black particles, which

are bound within the product matrix.".

Based upon the screening level assessment using testing data submitted by NPCA on the amounts of respirable silica produced from the normal use if interior flat latex paints,

OEHHA has decided to issue a safe use determination to NPCA for crystalline silica (quartz)

in interior latex paints.

The same method of encapsulation, as used for latex paints, is used for this product, Therefore, the crystalline silica (quartz) that is used in this product is not considered

hazardous.

Inhalation Specific test data for the substance or mixture is not available.

Eye contact Specific test data for the substance or mixture is not available.

Skin contact Specific test data for the substance or mixture is not available.

Ingestion Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity .

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 9,404.20 mg/kg

 ATEmix (dermal)
 4,630.50 mg/kg

 ATEmix (inhalation-gas)
 99,999.00 ppm

 ATEmix (inhalation-vapor)
 99,999.00 mg/l

 ATEmix (inhalation-dust/mist)
 99,999.00 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Asphalt (at Ambient Temperature) 8052-42-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 94.4 mg/m³ (Rat) 4.5 h
Kaolin 1332-58-7	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rat)	-
Bentonite 1302-78-9	> 5000 mg/kg (Rat)	-	-
Titanium Dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	= 5.09 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationNo information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Quartz 14808-60-7	A2	Group 1	Known	X
Titanium Dioxide	A3	Group 2B	-	X

13463-67-7

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

Occupational Safety and Health Administration of the US Department of Labor

X - Present

Reproductive toxicity No information available.

Developmental Toxicity None known for product as a whole.

None known. **Teratogenicity**

STOT - single exposure No information available.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Target organ effects Respiratory system, Eyes, Skin, Lungs, Gastrointestinal tract (GI).

No information available. **Aspiration hazard**

Other adverse effects N/A.

No information available. Interactive effects

12. Ecological information

Ecotoxicity

Toxicological testing has not been performed for this product overall. Available toxicological

data for individual ingredients is summarized below.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Bentonite 1302-78-9	-	LC50: =19000mg/L (96h, Oncorhynchus mykiss)	-	-

Persistence and degradability N/A.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Asphalt (at Ambient Temperature)	6
8052-42-4	

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations.

Contaminated packaging Do not reuse empty containers.

14. Transport information

Note: This material is not subject to regulation as a hazardous material for shipping

DOT Not regulated.

TDG Not regulated.

MEX Not regulated.

ICAO (air) Not regulated.

IATA Not regulated.

IMDG Not regulated.

15. Regulatory information

International Inventories

TSCA All of the components of this product are listed on the US TSCA (Toxic Substances Control

Act) Inventory or are exempt.

Chemical name	CAS No.	Inventory Listing Status	Commercial Activity Designation
Water	7732-18-5	Present	Active
Asphalt (at Ambient Temperature)	8052-42-4	Present	Active
Kaolin	1332-58-7	Present	Active
Bentonite	1302-78-9	Present	Active
Quartz	14808-60-7	Present	Active
Titanium Dioxide	13463-67-7	Present	Active

DSL/NDSL All of the components of this product are listed on the DSL.

EINECS/ELINCS All components are listed.

TCSI Contact supplier for inventory compliance status.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

TCSI - Taiwan Chemical Substance Inventory

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:.

Chemical name	California Proposition 65	
Quartz - 14808-60-7	Carcinogen	
Titanium Dioxide - 13463-67-7	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Water	-	-	X
7732-18-5			
Asphalt (at Ambient Temperature)	X	X	X
8052-42-4			
Kaolin	X	X	X
1332-58-7			
Calcium Carbonate	X	X	X
1317-65-3			
Quartz	X	X	X
14808-60-7			
Titanium Dioxide	X	X	X
13463-67-7			
QUARTZ	X	X	X
14808-60-7			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPAHealth hazards1Flammability1Instability0Special hazards-HMISHealth hazards1*Flammability1Physical hazards0Personal protection

Chronic Hazard Star Legend *= Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity ATE: Acute Toxicity Estimate LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

Sensitizers

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR) U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA) Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

World Health Organization

Prepared ByAIM Administrative Services Department.

Issuing Date 21-Jan-2025 Revision Date 21-Jan-2025

Revision Note Revised to comply with OSHA GHS Revision 7 of 2024.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.