



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Complies with OSHA GHS Revision 7 of 2024.

Issuing Date 22-Jan-2025

Revision Date 22-Jan-2025

Version 1

1. Identification

Product identifier

Product Name Emulsion Driveway Depression Filler - Trowel Grade

Other means of identification

Product Code AIM 925

Synonyms SEALANT

Recommended use of the chemical and restrictions on use

Recommended Use Used to fill cracks and prevents water penetration in cracks up to 1 inch wide.

Restrictions on use For exterior use only. Do not use indoors.

Details of the supplier of the safety data sheet

Supplier Address

American Industrial Manufacturers of Building Materials
W. Park Blvd
Suite 306-366
Plano, Texas 75093
(214) 254-4720

Emergency telephone number

Company Phone Number (214) 254-4720

Emergency Telephone Call CHEMTREC Day or Night:
Within USA and Canada: 1-800 424-9300
Outside USA and Canada: 1-703-527-3887

2. Hazard(s) identification

Classification

Carcinogenicity	Category 1A
-----------------	-------------

Hazards not otherwise classified (HNOC)

Not applicable.

Label elements



Danger

Hazard statements

May cause cancer.

Precautionary Statements - Prevention

Do not handle until all safety precautions have been read and understood.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical help.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice/attention.

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

Rinse mouth.

IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.

Precautionary Statements - Storage

Keep From Freezing.

Precautionary Statements - Disposal

Disposal should be in accordance with applicable local, regional, and national laws and regulations..

Other Information

No information available.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Common name Driveway crack filler.

Synonyms SEALANT.

Chemical nature Mixture of moisture reactive polymers, plasticizers and fillers.

Chemical name	CAS No.	Weight-%	Trade secret
Asphalt (at Ambient Temperature)	8052-42-4	30-35	*
Kaolin	1332-58-7	5-10	*
Silica, quartz	14808-60-7	5-10	*
Calcium Carbonate	1317-65-3	5-10	*
Bentonite	1302-78-9	1-5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice	This product presents no hazards under normal conditions of use.
Inhalation	No hazards which require special first aid measures.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash skin with soap and water.
Ingestion	Rinse mouth. Get medical attention if symptoms occur. Not an expected route of exposure.

Most important symptoms and effects, both acute and delayed

Symptoms	No information available.
Effects of Exposure	See Section 11 for additional Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
--------------------	------------------------

5. Fire-fighting measures

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	Non-combustible.
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.
Special protective equipment and precautions for fire-fighters	Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	None under normal use conditions.
----------------------	-----------------------------------

Methods and material for containment and cleaning up

Methods for containment	Prevent further leakage or spillage if safe to do so.
-------------------------	---

Methods for cleaning up	Pick up and transfer to properly labeled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing.
-------------------------	---

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep from freezing.
--------------------	---------------------

8. Exposure controls/personal protection

Control parameters

Exposure Limits	No ACGIH or OSHA PEL is assigned to this mixture. This product, as supplied, is not believed to contain any hazardous material that exceeds exposure limits established by OSHA. Exposure limits for the component materials are shown below.
-----------------	---

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Asphalt (at Ambient Temperature) 8052-42-4	TWA: 0.5 mg/m ³ Benzene-soluble aerosol fume, inhalable particulate matter	-	Ceiling: 5 mg/m ³ fume 15 min
Kaolin 1332-58-7	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Silica, quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust
Calcium Carbonate 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust

		(vacated) TWA: 5 mg/m ³ respirable fraction	
Bentonite 1302-78-9	TWA: 1 mg/m ³ respirable particulate matter	-	-

Biological occupational exposure limits

Chemical name	ACGIH
Asphalt (at Ambient Temperature) 8052-42-4	2.5 µg/L - urine (1-Hydroxypyrene with hydrolysis) - end of shift at end of workweek

Appropriate engineering controls

Engineering controls None under normal use conditions.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes.

Hand protection Wear suitable gloves.

Skin and body protection Long sleeved clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Thick mastic
Color	Black
Odor	Low
Odor threshold	Negligible odor.

Property	Values	Remarks • Method
pH	Not applicable	7.0
pH (as aqueous solution)		None known
Melting point/freezing point	None / 0 None / 32	Melting Point is not applicable. Freezing points are shown.
Boiling point / boiling range	> 100 °C / 212 °F	
Flash point	Not applicable	Non Flammable
Evaporation rate	The evaporation rate of the water component of this emulsion product is dependent upon: 1) The temperature of the water at the air-water surface; 2) The humidity of the air; 3) The area of the air-water surface; 4) The temperature of the air.	No data available. Evaporation rate is dependent upon atmospheric conditions.
Flammability (solid, gas)	Non Flammable	
Flammability Limit in Air		Not flammable
Upper flammability limit:	Not applicable	
Lower flammability limit:	Not applicable	

Vapor pressure	2.33 (kPa)	@ 20 °C
Vapor density	5.3	Where: Air = 1 at 68 degrees F (20 degrees C)
Relative density	1.4	Water = 1g/ml
Water solubility	No data available	Dispersible
Solubility(ies)	No data available.	Reacts with water to form carbon dioxide
Partition coefficient	No data available.	Insoluable
Autoignition temperature	330 °C / 626 °F	No data available.
Decomposition temperature		
Kinematic viscosity		
Dynamic viscosity	No data available.	@ 25 °C
Other information		
Explosive properties	No information available	
Oxidizing properties	No information available	
Softening point	Not applicable	
Molecular weight	N/A	
VOC Content (%)	Less than 50 g/l	
Density	11.3 to 11.7 lb/gal	
Bulk density	Not applicable	

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	Non-combustible, substance itself does not burn but may react upon heating to produce corrosive and/or toxic fumes.
Hazardous polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Do not freeze.
Incompatible materials	None known.
Hazardous decomposition products	N/A.

11. Toxicological information

Information on likely routes of exposure

Product Information	<p>The IARC Monograph (Vol. 103, 2013, Bitumen and Bitumen Emissions) defines Asphalt as 'Group 2B, Possible Carcinogen to Humans'. This definition is based on studies of exposure to Asphalt fumes at elevated temperatures. The Monograph states that temperature plays an important role in determining the degree of exposure and also the carcinogenic potential of bitumen emissions. This same Monograph states that Asphalt is non volatile at ambient temperature. There is no data presented in the Monograph to demonstrate that Asphalt at ambient temperature is considered a carcinogen. Since the normal use of this product is at ambient temperature, the Asphalt used in this product is not listed as a carcinogen. No other national or international agency has defined Asphalt as a carcinogen.</p> <p>Based upon the screening level assessment using testing data submitted by NPCA on the amounts of respirable silica produced from the normal use of interior flat latex paints, OEHHA has decided to issue a safe use determination to NPCA for crystalline silica (quartz) in interior latex paints.</p> <p>The same method of encapsulation, as used for latex paints, is used for this product. Therefore, the crystalline silica (quartz) that is used in this product is not considered hazardous.</p>
---------------------	--

Inhalation	Specific test data for the substance or mixture is not available.
Eye contact	Specific test data for the substance or mixture is not available.
Skin contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	8,980.50 mg/kg
ATEmix (dermal)	4,181.10 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-vapor)	99,999.00 mg/l
ATEmix (inhalation-dust/mist)	99,999.00 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Asphalt (at Ambient Temperature) 8052-42-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 94.4 mg/m ³ (Rat) 4.5 h
Kaolin 1332-58-7	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rat)	-
Bentonite 1302-78-9	> 5000 mg/kg (Rat)	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Silica, quartz 14808-60-7	A2	Group 1	Known	X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

Occupational Safety and Health Administration of the US Department of Labor

X - Present

Reproductive toxicity	No information available.
Developmental Toxicity	None known for product as a whole.
Teratogenicity	None known.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Target organ effects	Respiratory system, Eyes, Skin, Lungs, Gastrointestinal tract (GI).
Aspiration hazard	No information available.
Other adverse effects	N/A.
Interactive effects	No information available.

12. Ecological information

Ecotoxicity Toxicological testing has not been performed for this product overall. Available toxicological data for individual ingredients is summarized below.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Bentonite 1302-78-9	-	LC50: =19000mg/L (96h, Oncorhynchus mykiss)	-	-

Persistence and degradability N/A.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Asphalt (at Ambient Temperature) 8052-42-4	6

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations.

Contaminated packaging Do not reuse empty containers.

14. Transport information

Note: This material is not subject to regulation as a hazardous material for shipping

DOT Not regulated.

TDG Not regulated.

MEX Not regulated.

ICAO (air) Not regulated.

IATA Not regulated.

IMDG Not regulated.

15. Regulatory information

International Inventories

TSCA All of the components of this product are listed on the US TSCA (Toxic Substances Control Act) Inventory or are exempt.

Chemical name	CAS No.	Inventory Listing Status	Commercial Activity Designation
Water	7732-18-5	Present	Active
Asphalt (at Ambient Temperature)	8052-42-4	Present	Active
Kaolin	1332-58-7	Present	Active
Silica, quartz	14808-60-7	Present	Active
Calcium Carbonate	1317-65-3	Present	Active
Wollastonite	14983-17-0	-	Unknown *
Bentonite	1302-78-9	Present	Active

DSL/NDSL All of the components of this product are listed on the DSL.

EINECS/ELINCS All components are listed.

TCSI Contact supplier for inventory compliance status.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

TCSI - Taiwan Chemical Substance Inventory

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:.

Chemical name	California Proposition 65
Silica, quartz - 14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Water 7732-18-5	-	-	X
Asphalt (at Ambient Temperature) 8052-42-4	X	X	X
Kaolin 1332-58-7	X	X	X
Calcium Carbonate 1317-65-3	X	X	X
Silica, quartz 14808-60-7	X	X	X
QUARTZ 14808-60-7	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA	Health hazards 1	Flammability 1	Instability 0	Special hazards -
HMIS	Health hazards 1*	Flammability 1	Physical hazards 0	Personal protection -

Chronic Hazard Star Legend

* = Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
STOT: Specific Target Organ Toxicity
ATE: Acute Toxicity Estimate
LC50: 50% Lethal Concentration
LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
+	Sensitizers		

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGL(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Prepared By	AIM Administrative Services Department.
Issuing Date	22-Jan-2025
Revision Date	22-Jan-2025
Revision Note	Revised to comply with OSHA GHS Revision 7 of 2024.
<u>Disclaimer</u>	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.