



PRODUCT DATA SHEET

#925 Emulsion Driveway Depression Filler – Trowel Grade

DESCRIPTION

AIM #925 Emulsion Driveway Depression Filler - Trowel Grade is a heavy-bodied sealant formulated to remain strong and flexible when properly applied to a driveway surface. AIM #925 is fortified with mineral fillers to add reinforcement. It blends with the blacktop surface to prevent water seepage and the damage that can caused by erosion as well as freeze/thaw cycles. Driveway repair dramatically increases the life of the asphalt surface. Once cured, AIM #925 may be top coated with either Coal Tar or Asphalt based driveway sealers.

USES

Fills cracks and prevents water penetration in cracks up to 1" wide.

PREPARATION: Remove all dust, dirt, debris and loose particles with a stiff brush or broom. If air pressure is available, blow cracks clean and dry. Do not apply when rain is forecasted or when the ambient air temperature is expected to fall below 50°F (10°C) within 48 hours.

APPLICATION

Do not thin. Use AIM #925 directly as supplied. Press AIM #925 directly into cracks using a putty knife or squeegee. Use firm pressure to insure all voids are sealed. The finished surface may be smooth using a putty knife. AIM #925 will cure to a resilient black sealant in 24-48 hours.

TIPS:

For best results, cracks deeper than ½" should be sealed in two layers allowing 24 hours between applications.

Keep traffic off the repair area if possible during the curing period. If immediate use is required, fill crack to ¼" from top surface and lightly cover AIM #925 with sand. This will prevent tracking.

Clean wet coating with soap and water. Dry coating may be removed with mineral spirits. Use care when handling solvents.

KEEP FROM FREEZING

CAUTION

Do not take internally. Avoid prolonged contact with skin or fumes. If irritation occurs seek medical attention. If swallowed, do not induce vomiting.

KEEP OUT OF REACH OF CHILDREN.

First Aid: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

Warning: This product contains a chemical known to the State of California to cause cancer.

LIMITED WARRANTY

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of 12 months from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application.

LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.



6505 West Park Boulevard • Suite 306-366 • Plano, TX 75093 • (214) 254-4720