



# PRODUCT DATA SHEET

## #115 Acrylic Bonding Primer

### DESCRIPTION

AIM #115 Acrylic Bonding Primer is an acrylic water-based elastomeric super primer. This primer base is a modified acrylic latex polymer for self-crosslinking and offers outstanding flash rust resistance. This primer reduces absorbency of subsequent coatings and enhances adhesion bond quality. This quick-drying clear super primer has excellent long-term durability, and provides outstanding adhesion to tough substrates and surfaces.

### USES

AIM #115 Acrylic Bonding Primer's creative formulation makes it a very versatile water-based primer. This primer has excellent adhesion over most single ply membranes, smooth and or granulated APP, TPO, SBS, metal, and carbon steel, Not recommended over BUR systems or mopping asphalt. Can be applied over asphalt emulsion surfaces. AIM #115 Acrylic Bonding Primer aids in the adhesion of acrylic coatings.

### SURFACE PREPARATION

Surfaces must be cleaned, dried, and free of moisture on and beneath the surface. Remove dust, dirt, oil, loose granules, and any other foreign contaminants. Surfaces with mildew growth must be cleaned with AIM #110 Detergent Primer or a bleach solution; then rinsed thoroughly. Rusted metal should be cleaned with a wire brush. Pressure washing surface is recommended for best results. Repair all holes, leaks, and cracks with AIM #740 White Acrylic Mastic and polyester fabric in the Three Course Installation Method. Acceptance of the substrate is the sole decision of the owner or appointed representative

### APPLICATION

For exterior use only. Apply on warm, sunny day preferably in the morning to provide maximum cure time. AIM #115 must be applied to a dry surface. Prior to application water must be swept out of all puddles, waterways, and birdbaths. Temperature should be 55°F and rising. Stir thoroughly before application to achieve a uniform consistency.

Apply with a professional spray equipment. Apply one coat at a rate of 0.5 gallons per square. Allow a minimum of 4 hours to dry and 24–48 hours for full cure, dependent upon weather conditions.

Clean wet coating with soap and water. Dry coating may be removed with mineral spirits. Use care when handling solvents.

### CAUTION

Read latest product Safety Data Sheet for full list of any hazards, precautionary statements, or safety data related to this product.

Do not take internally. Avoid prolonged contact with skin or fumes. If irritation occurs seek medical attention. If swallowed, do not induce vomiting.

### KEEP OUT OF REACH OF CHILDREN.

**First Aid:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention if symptoms occur; for skin, wash thoroughly with soap and water.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

### Precautions

DO NOT STORE AT TEMPERATURES BELOW 50°F (10°C) OR ABOVE 120°F (49°C).

DO NOT ALLOW TO FREEZE.

DO NOT APPLY WHEN HEAVY DEW OR RAIN IS EXPECTED WITHIN 24 HOURS.

DO NOT THIN.

When transporting this product, be sure the lid is tight and the pail is secured. Do not allow pail to tumble as this may loosen the lid and cause leakage or spillage.

Drying time may vary depending upon wet film thickness, temperature, humidity, and air movement

Container sizes

5 Gallon (19 L) Pails, 55 Gallon (208 L) Drums

#### **LIMITED WARRANTY**

**TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.**

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of 12 months from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application.

**LIMITATION OF LIABILITY:** In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental, or consequential damages, whether based on contract, tort (including negligence), or any other legal theory.



**6505 West Park Boulevard • Suite 306-366 • Plano, TX 75093 • (214) 254-4720**