



PRODUCT DATA SHEET

SP-100 Shingle Revitalizer - Concentrate

DESCRIPTION

AIM SP-100 Shingle Revitalizer- Concentrate is a unique, water-based revitalizing shingle coating designed to give longer life to asphalt shingles. Its dual action nature adds back revitalizing oils to the asphalt shingle while sealing and locking in the roof granules to restore and seal roofs from weathering. By giving back the oils needed to keep the shingle more like its original state while sealing the granules against weathering and erosion, AIM SP-100 Shingle Revitalizer Concentrate literally adds years of life to shingled roofs.

USES

Apply AIM SP-100 only to new or aged asphalt shingle surfaces. If the shingles are falling off the roof or the fiberglass reinforcement of the shingles is showing (signs of extreme shingle degradation), then the use of this product is not recommended. Please contact the AIM technical service department with questions about where this product is best used.

ADVANTAGES

- **WATERBASED** Easy clean up. Just use soap and water.
- **OUTSTANDING ADHESION AND DURABILITY** Long-lasting and bonds extremely well to properly prepared asphalt shingle surfaces.
- **NO DANGEROUS CHEMICALS** Does not contain any harmful chemicals or volatile organic compounds (VOC's) or solvents.
- **SUSTAINABLE** Made from bio-based components, AIM SP-100 Shingle Revitalizer is environmentally friendly.
- **PENETRATES AND SEALS** Proper application rate of the product on dry or damp shingles allows the oil portion to penetrate deep into the shingle, bringing back lost oils in the asphalt layer lost due to weathering and erosion.

PREPARATION

AIM SP-100 can be used on shingles made of asphalt. Do not apply to areas where ponded water exists. May be applied to dry or damp or shingles covered in dew as the product is water-based. Do not apply when it is raining or if rain is forecasted 4 hours or less from end of application. Apply between 50°F - 100°F.

MIXING

AIM SP-100 is provided in a concentrated form. Thin the concentrate material with water by volume, 2 parts water to 1 part of concentrate, then mix well (use mechanical or hand stirring 3-5 minutes once diluted) prior to applying by spray or roller.

APPLICATION

AIM S-100 can be applied by thick nap roller (1/2-3/4-inch nap) or by pump or electric sprayers. Best application rate and coverage is achieved when spray applied. Avoid puddling of material. Apply a thick, even coat that will appear uniformly white on the applied surface before moving to the next section. Product will then dry clear.

APPLICATION NOTES

Apply in one or two coats, ensuring an even, heavier coating that will appear white after application. Do not apply too heavily to avoid material running. Apply only enough to give a uniform white coat prior to moving to next section.

Avoid puddling of material. Do not apply in standing or puddled water. Do not apply in cold temperatures (<50°F) or in high heat (>100 °F)

Coverage: 200-300 square feet/gallon. NOTE: Coverage rates will vary depending on age and condition of shingled surface.

Clean wet coating with soap and water.

KEEP FROM FREEZING

KEEP OUT OF REACH OF CHILDREN.

CAUTIONS

See Safety Data Sheet for full list of cautionary statements.

First Aid: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention if symptoms occur; for skin, wash thoroughly with soap and water.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

PROPERTIES:

Dry to touch:	<2 hours
Appearance:	White when applied, clear when fully dried
VOC (g/l):	Zero to trace
Recoat interval:	Re-application of AIM SP-100 is recommended every 3 years to restore shingles to a newer state.
Shelf life:	1 year in unopened container stored between 50°F - 90°F.

Container sizes

5 Gallon (19 L) Pails

55 Gallon (208 L) Drums

LIMITED WARRANTY

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of 12 months from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application.

LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers' sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental, or consequential damages, whether based on contract, tort (including negligence), or any other legal theory.



6505 West Park Boulevard • Suite 306-366 • Plano, TX 75093 • (214) 254-4720